

DECLARATION OF PERFORMANCE

Woodio Solid Surface

1. Unique identification code of the product-type:

| Product Model | Description | | | |
|----------------|------------------------|--|--|--|
| No. | | | | |
| Woodio Solid12 | Solid surface panel | | | |
| (SS-SS12) | for decorative use, or | | | |
| | for interior fitments | | | |
| | (including furniture) | | | |

2. Type of the construction product

Decorative panel or furniture panel

3. Intended use

Interior decoration and fitments, solid surface use

4. Name and contact address of the manufacturer

Woodio Oy Hankasuontie 8 FI-00390 Helsinki, Finland woodio@woodio.fi +358 (0)50 478 2944

5. Where applicable, name and contact address of the authorized representative

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR (305/2011/EU), Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Determination of product type and factory production control by the manufacturer

8. Declared performance

Signed for and on behalf of the manufacturer by:

Jam len

Johanna Normiala Chief Technology Officer

| Essential Characteristics | Performance | Harmonized technical specification | | |
|------------------------------|----------------|--|--|--|
| Reaction to fire | NPD | | | |
| Release of | Does not | | | |
| formaldehyde | contain | | | |
| Release of other | Does not | | | |
| dangerous | contain | | | |
| substances | Contain | | | |
| Release of vinyl | | EN 15102:2007 | | |
| chloride | Does not | +A1:2011 | | |
| monomer | contain | | | |
| (VCM) | | | | |
| Sound | Not applicable | | | |
| absorption | Not applicable | | | |
| Thermal | 120°C for 1 | | | |
| resistance | hour | | | |
| Bending | Pass | | | |
| strength | F 033 | | | |
| Modulus of | | | | |
| elasticity in | Pass | | | |
| bending | | EN 312: 2010 | | |
| Tensile | | Type P2 | | |
| strength, | Pass | | | |
| perpendicular | | | | |
| Surface | Pass | | | |
| soundness | . 433 | | | |
| Tensile | | | | |
| strength, | 14,0 MPa | ISO527-1 | | |
| longitudinal | | | | |
| Impact strength | 1731 J/m2 | ASTM D256 | | |

9.

The performance of the products identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

| | 06 | .09.2 | 023 | | |
|--|----|-------|-----|------|--|
| | | | | | |
| | | | | | |

Date of issue